

Cable Socks

For Pulling & Supporting Cables, Hoses, Rods, Ropes & Tubes Etc.

Multiple Strength Pulling Grips with non-rotating Flexible Eye (OE Type)

For stringing or pulling-in non-insulated conductors on long, high voltage transmission lines or shorter, lower voltage distribution lines.



Single Eye (SE Type)

Available in single, double or triple weave sock.



Double Eye (DE Type)

Standard support grip closed with double eye. Available in single weave or double weave.



Standed wire mesh for flexibility and strengty?

Grip perits cable to breathe (expand or contract) without loss of holding action.

Open Ended (Type OE) or Midspan

Double ended grips designed to enable two cables, hoses or ropes to be fastened together for pulling or supporting purposes.



SELECTION DATA FOR STANDARD RANGE OF CABLE SOCKS

SOCK TYPE AND REFERENCE				DIMENSIONS (Approximate)								Proof Load
Single Eye	Double* Eye	Fleeting* Eye	Open* Ended	Cable Dia.		Overall Length				Lattice Length		
						SE	DE	FE	OE	SE, DE & FE	OE	
SE1	OE1	FE1	OE1	mm	6 - 13	305	305	305	380	230	380	0.51 Tonnes
				ins	¼ - ½	12"	12"	12"	15"	9"	15"	0.5 Tons
SE2	OE2	FE2	OE2	mm	13 - 19	430	430	430	610	355	610	1.02 Tonnes
				ins	½ - ¾	17"	17"	17"	24"	14"	24"	1.0 Tons
SE3	OE3	FE3	OE3	mm	19 - 25	510	485	510	710	405	710	1.02 Tonnes
				ins	¾ - 1	20"	19"	20"	28"	16"	28"	1.0 Tons
SE4	OE4	FE4	OE4	mm	25 - 38	610	585	610	815	455	815	2.54 Tonnes
				ins	1 - 1½	24"	23"	24"	32"	18"	32"	2.5 Tons
SE5	OE5	FE5	OE5	mm	38 - 50	735	710	735	915	535	915	2.54 Tonnes
				ins	1½ - 2	29"	28"	29"	36"	21"	36"	2.5 Tons
SE6	OE6	FE6	OE6	mm	50 - 63	865	840	865	1065	610	1065	3.05 Tonnes
				ins	2 - 2½	34"	33"	34"	42"	24"	42"	3.0 Tons
SE7	OE7	FE7	OE7	mm	63 - 89	990	915	990	1220	685	1220	3.05 Tonnes
				ins	2½ - 3½	39"	36"	39"	48"	27"	48"	3.0 Tons
SE8	OE8	FE8	OE8	mm	89 - 115	990	915	990	1370	685	1370	3.56 Tonnes
				ins	3½ - 4½	39"	36"	39"	54"	27"	54"	3.5 Tons

*Styles DE, FE and OE can, if required, be supplied split complete with lace for those applications where it is not possible to apply the cable sock in the normal way. When so required, please add suffix 'SL' to Style Number when ordering.